

Extreme Energy Solutions  
Material Safety Data Sheet  
Extreme Xtra Gasoline Treatment  
US EPA REG. NO 2491-20002

---

Extreme Energy Solutions  
150 Main Street  
Ogdensburg, NJ 07439  
973 209 3450

---

US EPA REG. NO 2491-20002

---

PHYSICAL CHEMICAL IDENTITY AND PROPERTIES SECTIONS II & III

---

Chemical Name: Hydrocarbons plus additives

Formula: N/A

Hazardous Decomposition of Products: Carbon Monoxide and carbon dioxide if burned. Oxides from burning.

Hazardous or Toxic Ingredients: None

Form: Liquid    Odor: Light Petroleum    Appearance: Liquid    Color: Amber

Specific Gravity (water=1) : .89

Boiling Point: Greater than 370 degrees C (700 degree F)

Melting Point: -18 degrees C (0 degrees F)

Solubility in Water (by weight %): -0-@20 degrees C

Volatile (by weight %): -0-

Evaporation Rate: -0-

Vapor Pressure (mm Hg @ 20 degrees C): -0-

PH (as is): N/A

Stability: Stable under normal conditions

Viscosity cSt @ 100 degrees C: Greater than or = to 10

---

FIRE AND EXPLOSION HAZARD DATA - SECTION IV

---

Special Fire Extinguishing Procedure (air): Do not use water except as fog.

Unusual Explosion and Fire Hazards: None

Flashpoint: (Method Used) Cleveland Open Cup - Greater than 205 degrees C (400 degrees F)

Flammable Limits %: N/A

Extinguishing Agent: Dry chemical, water fog, CO2 or foam. Closed containers exposed to fire should be cooled with water.

---

HEALTH HAZARD DATA - SECTION V

---

Permissible Concentration (air): Product should not be used other than specified. However, if used in applications where a mist might be generated, observe a TWA/PEL of 5 mg/m for mineral oil mist (OSHA and ACGIH)

Chronic Effects of Over - Exposure: Prolonged or repeated skin contact may cause skin irritation (dermatitis)

Acute Toxicological Properties: No Data Available

Emergency First Aid Procedures:

Eyes: Flush with ample amounts of water for 15 minutes. If irritation persists, call a physician.

Skin: Remove excess with cloth or paper. Wash thoroughly with soap and water.

Inhalation: Remove victim to fresh air. Call a physician.

Ingestion: Contact a physician immediately.

---

## SPECIAL PROTECTION INFORMATION - SECTION VI

---

Ventilation type required (local, mechanical, special): None.

Respiratory Protection (specify types): None.

Protective Gloves: Neoprene type for bulk handling.

Eye Protection: Chemical Safety goggles for bulk handling.

Other Protective Equipment: None.

---

EXTREME XTRA DIESEL FUEL TREATMENT PRODUCT CODE: 857774002002

---

## SPECIAL PRECAUTIONS - SECTIONS VII

---

Handling and Storage Precautions: Do not handle or store at temperatures above 100 degrees C (221 degrees F)

Maximum Storage Temperature: 100 degrees C (212 degrees F)

---

## TRANSPORTATION DATA - SECTION VIII

---

DOT : Hydrocarbon Liquid UN3295

Reportable Quantity: N/A

Freight Classification: Petroleum Lubrication Oil

Special Transportation Notes: None.

---

Prepared by: Samuel Burlum

Title: CEO/President

Original Date: April 21, 2010

---

It is our belief that the statements, technical information and recommendations contained herein are reliable, however they are given without warranty or guarantee of any kind, expressed or implied and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use due to customers mishandling or negligence.

---

Extreme Xtra Diesel Treatment is available in the following configurations:

16 ounce applicator bottle with fill chamber foil sealed safety cap.

Bar code: 857774002002